

ATF POWER DX III

Automatic transmission fluid

ATF POWER DX III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

ATF POWER DX III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF POWER DX III meets the following performance criteria:

DEXRON III F/G/H	Allison C4	CAT TO-2	MAN 339 Z1/Z2
MAN 339 V1/V2	MB 236.10/236.9/236.7/236.5/236.1		Voith 55.6335
Volvo 97341	Mercon	ZF 02F/03D/04D	ZF 11A/11B/14B/16L

Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15°C	kg/m ³	ASTM 4052	845
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	35
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	189
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
Date Issued: 26-1-2021	Supersedes: 01-11-2016	Revision Nr.: 02	



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 73220 - ATF POWER DX III
Product code : 73220

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use, Industrial use, Professional use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

North Sea Lubricants B.V. B.V.
Ampèrestraat 5
NL- 3846AN Harderwijk
The Netherlands
T +31 651345369
support@northsealubricants.com - www.northsealubricants.com

1.4. Emergency telephone number

Emergency number : +31 (0)786527652
Monday to Friday: 09:00 - 16:00 (CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil substance with national workplace exposure limit(s) (BE, BG, CZ, DK, HR, NL, NO); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	50 – 75	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil substance with national workplace exposure limit(s) (BG, CZ, DK, HR, NL); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	10 – 25	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light naphthenic; Baseoil	CAS-No.: 64742-53-6 EC-No.: 265-156-6 EC Index-No.: 649-466-00-2 REACH-no: 01-2119480375-34	0.1 – 2.5	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic; Baseoil substance with national workplace exposure limit(s) (BE, NL)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	0.1 – 2.5	Not classified
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil substance with a Community workplace exposure limit	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	0.1 – 2.5	Asp. Tox. 1, H304
Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates substance with a Community workplace exposure limit	EC-No.: 417-450-2 EC Index-No.: 650-042-00-4 REACH-no: 01-0000016426-70	0.1 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use. May cause an allergic skin reaction.
Symptoms/effects after skin contact	: Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis.
Symptoms/effects after eye contact	: May cause eye irritation.

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
- Symptoms/effects upon intravenous administration : No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread. Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Handling temperature : < 40 °C
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: < 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³
Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	10 mg/m ³
IOEL STEL	5 mg/m ³
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil (72623-87-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	6 (> 480 minutes)	>0.35	3 (> 0.65)	EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: -42
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 171 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 34.75 mm ² /s @40°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 863.7 kg/m ³ @15°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h
Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates	
LD50 oral (rat)	> 2000 mg/kg

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates	
LD50 dermal (rabbit)	> 2000 mg/kg bodyweight Animal: other:Rabbit (New Zealand White)
Distillates (petroleum), hydrotreated light naphthenic; Baseoil (64742-53-6)	
LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5.7 mg/l/4h
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight
Distillates (petroleum), hydrotreated light naphthenic; Baseoil (64742-53-6)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified
Additional information : Based on available data, the classification criteria are not met

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

73220 - ATF POWER DX III

Viscosity, kinematic	34.75 mm ² /s @40°C
----------------------	--------------------------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata

Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates

EC50 72h - Algae [1]	22 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
----------------------	---

Distillates (petroleum), hydrotreated light naphthenic; Baseoil (64742-53-6)

LC50 - Fish [1]	> 100 mg/l (fathead minnow - Pimephales promelas, OECD TG 203)
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata, OECD TG 201
NOEC (chronic)	> 10 mg/l Daphnia magna
NOEC chronic fish	> 5000 mg/l Pimephales promelas

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	≥ 1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata
--------------------	--

12.2. Persistence and degradability

73220 - ATF POWER DX III

Persistence and degradability	Not established.
-------------------------------	------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Biodegradation	31 % 28 d OECD 301F
----------------	---------------------

Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Biodegradation	0.284 % 28D, OECD TG 301 B
----------------	----------------------------

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

Biodegradation	31 % 28 d OECD 301F
----------------	---------------------

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

Biodegradation	31 % 28 d, OECD TG 301 F
----------------	--------------------------

12.3. Bioaccumulative potential

73220 - ATF POWER DX III

Bioaccumulative potential	Not established.
---------------------------	------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9.2
---	-----

Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates

Partition coefficient n-octanol/water (Log Pow)	> 6.5
---	-------

Distillates (petroleum), hydrotreated light naphthenic; Baseoil (64742-53-6)

Partition coefficient n-octanol/water (Log Pow)	> 6
---	-----

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	> 6
---	-----

12.4. Mobility in soil

Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list $\geq 0,1$ % / SCL

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the Canadian NDSL (Non-Domestic Substances List)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Added	
	Flammability (solid, gas)	Modified	
	SDS Ref.	Removed	
1.2	Industrial/Professional use spec	Added	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures general	Added	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after inhalation	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
4.2	Symptoms/effects	Added	
4.2	Symptoms/effects upon intravenous administration	Added	
4.2	Symptoms/effects after skin contact	Added	
4.2	Symptoms/effects after inhalation	Added	
4.2	Symptoms/effects after ingestion	Added	

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
4.2	Symptoms/effects after eye contact	Added	
5.1	Unsuitable extinguishing media	Added	
5.3	Protection during firefighting	Modified	
5.3	Firefighting instructions	Added	
5.3	Precautionary measures fire	Added	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Added	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Methods for cleaning up	Modified	
6.4	Reference to other sections (8, 13)	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
7.2	Incompatible products	Added	
7.2	Incompatible materials	Added	
8.2	Personal protective equipment	Modified	
8.2	Hand protection	Modified	
8.2	Other information	Added	
8.2	Materials for protective clothing	Added	
8.2	Skin and body protection	Modified	
8.2	Appropriate engineering controls	Modified	
8.2	Eye protection	Modified	
8.2	Respiratory protection	Modified	
9.1	Density	Modified	
9.1	Odour	Added	
9.1	Solubility	Added	
10.2	Chemical stability	Modified	
10.3	Possibility of hazardous reactions	Modified	
10.4	Conditions to avoid	Modified	
10.5	Incompatible materials	Added	
10.6	Hazardous decomposition products	Modified	
11.1	Additional information	Added	
11.1	Additional information	Added	
11.1	Additional information	Added	
11.1	Additional information	Added	
11.1	Additional information	Added	
11.1	Additional information	Added	
11.1	Additional information	Added	

73220 - ATF POWER DX III

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
11.1	Additional information	Added	
11.1	Additional information	Added	
11.1	Potential adverse human health effects and symptoms	Added	
12.2	Persistence and degradability	Added	
12.3	Bioaccumulative potential	Added	
13.1	Waste disposal recommendations	Added	
13.1	Ecology - waste materials	Added	
16	Data sources	Added	
16	Other information	Added	
16	Abbreviations and acronyms	Added	

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.