

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer HYD AW VG 22, 32, 46, 68, 100, 150

Description

XTeer HYD AW is the best anti-wear hydraulic oil. It is formulated with excellent quality base oil technology and an additive system that provides exceptional oxidation stability, water separability and foam suppression. It is especially exceptional for anti-wear protection.

Application

Recommended for applications calling for anti-wear, rust and oxidation inhibited Additives including

- ✧ Hydraulic systems
- ✧ Industrial bearings
- ✧ Circulating systems, splash, bath and ring lube systems for bearings and gears
- ✧ A myriad of assorted industrial applications: hoists, machine tools, etc.
- ✧ Gear sets not requiring an EP gear oil
- ✧ Bath, splash circulating or mist systems

Features / Benefits

- ✧ Protection against oxidation
- ✧ Protection against rust and corrosion
- ✧ Low foaming
- ✧ Outstanding wear protection.

Remarks

XTeer AW meets or exceeds the requirements of

- ✧ DIN 51524 part2



XTeer AW VG		22	32	46	68	100	150
Density (15°C, kg/m ³)		859.4	855.9	867.2	870.5	876.3	876.6
Viscosity	40°C	22.1	32.5	46.2	66.9	99.3	148.1
	100°C	4.34	5.52	6.99	8.91	11.55	15.3
Viscosity Index		103	106	108	107	104	104
Flash Point (°C)		203	231	236	251	268	251
Pour Point (°C)		-25	-25	-25	-25	-25	-25