

AUTOGEAR POWER TX 75W-80

Fully Synthetic Universal Transmission Oil

AUTOGEAR POWER TX 75W-80 is a high-quality fuel saving synthetic thermally stable long life gear lubricant designed for passenger- and commercial vehicles using manual transmissions fitted with different synchronizers including latest ones based on carbon.

AUTOGEAR POWER TX 75W-80 is based on high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability
- Superior lubricating properties provide improved fuel economy
- Exceptional load bearing characteristics
- Effective rust and corrosion protection
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures
- Good gear engagement with a variety of synchronizer materials including latest carbon
- Good frictional properties provide improved fuel economy and smoother shift ability

AUTOGEAR POWER TX 75W-80 meets the following performance criteria:

Approved: MAN 341 Z4

Meets: API GL-4
Renault B0032/2

Volvo 97307
Eaton Europe

DAF
Iveco

ZF TE-ML 01L,02L,08,13,16K,24A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	75W-80
Density @15°C	kg/m ³	ASTM 4052	862
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	59.4
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	9.9
Viscosity Index		ASTM D2270	153
Brookfield Viscosity @-40°C	cP	ASTM D2983	150000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Date Issued: 17-2-2021	Supersedes: 30-03-2018	Revision Nr.: 03	



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 73330 - AUTOGEAR POWER TX 75W-80
Product code : 73330
Type of product : Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use
Industrial/Professional use spec : Industrial
For professional use only
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

North Sea Lubricants B.V. B.V.
Ampèrestraat 5
NL- 3846AN Harderwijk
The Netherlands
T +31 651345369
support@northsealubricants.com - www.northsealubricants.com

1.4. Emergency telephone number

Emergency number : +31 (0)786527652
Monday to Friday: 09:00 - 16:00 (CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl, 2-Ethylhexyl methacrylate (688-84-6). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards which do not result in classification : Flammable liquids. Prolonged or repeated contact may cause dermatitis by loss of natural skin fats. Spills of this product present a serious slipping hazard.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil substance with national workplace exposure limit(s) (BE, BG, CZ, DK, HR, NL, NO); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 75	Asp. Tox. 1, H304
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	CAS-No.: 36878-20-3 EC-No.: 253-249-4 REACH-no: 01-2119488911-28	0.5 – 2.5	Aquatic Chronic 4, H413 (M=0)
Distillates (petroleum), hydrotreated light paraffinic; Baseoil substance with national workplace exposure limit(s) (BE, NL)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	0.1 – 2.5	Not classified
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	0.5 – 1	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
2-Ethylhexyl methacrylate	CAS-No.: 688-84-6 EC-No.: 211-708-6 REACH-no: 01-2119490166-35	0.01 – 0.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Eliminate all ignition sources if safe to do so.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage temperature : < 45 °C
Storage area : Store away from heat. Store in a well-ventilated place.
Special rules on packaging : Keep only in original container. Store in a closed container.

7.3. Specific end use(s)

No additional information available

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m ³
----------	---------------------

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Hand protection:

Breakthrough time : refer to the recommendations of the supplier. Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143. Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: -36 °C
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 220 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 56 mm ² /s @40°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 859 kg/l
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Reaction products of Benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rat)	> 2000 mg/kg

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h

Skin corrosion/irritation : Not classified
Additional information : Based on available data, the classification criteria are not met
Serious eye damage/irritation : Not classified
Additional information : Based on available data, the classification criteria are not met
Respiratory or skin sensitisation : Not classified
Additional information : Based on available data, the classification criteria are not met
Germ cell mutagenicity : Not classified
Additional information : Based on available data, the classification criteria are not met
Carcinogenicity : Not classified
Additional information : Based on available data, the classification criteria are not met
Reproductive toxicity : Not classified
Additional information : Based on available data, the classification criteria are not met

2-Ethylhexyl methacrylate (688-84-6)

NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
NOAEL (animal/female, F0/P)	300 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

STOT-single exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

2-Ethylhexyl methacrylate (688-84-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

NOAEL (oral, rat, 90 days) 150 mg/kg bodyweight/day

2-Ethylhexyl methacrylate (688-84-6)

NOAEL (oral, rat, 90 days) 120 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

73330 - AUTOGEAR POWER TX 75W-80

Viscosity, kinematic 56 mm²/s @40°C

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

LC50 - Fish [1] 24 mg/l (Oncorhynchus mykiss, 96h) (OECD 203 method)

LC50 - Fish [2] 8.5 mg/l Pimephales promelas

EC50 - Crustacea [1] 91.4 mg/l Daphnia magna

EC50 72h - Algae [1] 6.4 mg/l selenastrum capricomutum

NOEC chronic fish 3.2 mg/l Oncorhynchus mykiss

NOEC chronic crustacea 0.12 mg/l Daphnia magna

NOEC chronic algae 1.7 mg/l selenastrum capricomutum

2-Ethylhexyl methacrylate (688-84-6)

LC50 - Fish [1] 2.78 mg/l

EC50 - Crustacea [1] 0.105 mg/l

EC50 72h - Algae [1] 7.68 mg/l

NOEC chronic crustacea 0.105 mg/l

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Ethylhexyl methacrylate (688-84-6)	
NOEC chronic algae	0.28 mg/l
Reaction products of Benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
LC50 - Fish [1]	> 100 mg/l Danio rerio
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Desmodesmus subspicatus
NOEC chronic algae	> 10 mg/l Desmodesmus subspicatus
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	≥ 1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata
12.2. Persistence and degradability	
73330 - AUTOGEAR POWER TX 75W-80	
Persistence and degradability	Not established.
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	
Biodegradation	7.4 % 28 DY, OECD TG 301 B
2-Ethylhexyl methacrylate (688-84-6)	
Persistence and degradability	Biodegradable.
Biodegradation	88 % 28 Days
Reaction products of Benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 %
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
Biodegradation	31 % 28 d, OECD TG 301 F

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

73330 - AUTOGEAR POWER TX 75W-80

Bioaccumulative potential	Not established.
---------------------------	------------------

2-Ethylhexyl methacrylate (688-84-6)

Bioconcentration factor (BCF REACH)	1.6
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Kow)	4.95
---	------

Reaction products of Benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

Bioconcentration factor (BCF REACH)	1584.89
-------------------------------------	---------

Partition coefficient n-octanol/water (Log Pow)	> 7
---	-----

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	> 6
---	-----

12.4. Mobility in soil

Reaction products of Benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
2.1	Adverse physicochemical, human health and environmental effects	Added	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after inhalation	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
4.3	Other medical advice or treatment	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Modified	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Other information	Added	
6.3	Methods for cleaning up	Modified	
6.4	Reference to other sections (8, 13)	Modified	
7.1	Hygiene measures	Added	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
8.2	Environmental exposure controls	Added	
8.2	Appropriate engineering controls	Added	
8.2	Skin and body protection	Added	
8.2	Personal protective equipment	Modified	
8.2	Eye protection	Modified	
8.2	Hand protection	Modified	
9.1	Melting point	Added	
10.1	Reactivity	Added	
12.1	Ecology - general	Added	
13.1	Waste treatment methods	Added	
16	Abbreviations and acronyms	Added	

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information

: None.

73330 - AUTOGEAR POWER TX 75W-80

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl, 2-Ethylhexyl methacrylate(688-84-6). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.