

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer R&O VG 32, 46, 68

Description

XTeer R&O is a rust and oxidation inhibited hydraulic oil. It is formulated with select additives and designed for used in a variety of industrial applications. It is also suitable for use in applications where a premium R&O product is not required.

Application

- ✧ Applications where a straight mineral oil is required without extreme pressure (EP), detergent, dispersant or anti-wear additives.
- ✧ General machine oil
- ✧ Low pressure circulating fluid
- ✧ Non-Critical hydraulic applications
- ✧ Air-tool oil
- ✧ Drip or splash lubricant
- ✧ Spindle Oil
- ✧ Lubrication of light-duty compressors

XTeer R&O VG		Test method	32	46	68
Density (15°C, kg/m ³)		ASTM D1298	863.7	867.2	871.5
Viscosity	40°C	ASTM D445	32.7	46.4	69.3
	100°C	ASTM D445	5.61	7.0	9.23
Viscosity Index		ASTM D2270	110	110	109
Flash Point (°C)		ASTM D92	228	230	230
Pour Point (°C)		ASTM D97	-32.5	-32.5	-27.5

Features / Benefits

- ✧ Protection against oxidation
- ✧ Protection against rust and corrosion
- ✧ Low foaming

Remarks

XTeer R&O meets or exceeds the requirements of

- ✧ Parker Hannifin France HF-1,
- ✧ DIN 51524 Part 1, MIL-H-17672D
- ✧ U.S. Steel 126, AFNOR E46-800 HL
- ✧ Cincinnati Machine P-38, P-54, P-55